

900mm Black and White Bollard 60mm - 193mm Diameter Concrete In



Part Number	Description	Weight
138 121 114BW	60mm Black & White	5kg
138 121 241BW	76mm Black & White	6kg
138 121 290BW	90mm Black & White	7kg
138 121 314BW	101mm Black & White	9kg
138 121 414BW	114mm Black & White	10kg
138 121 524BW	127mm Black & White	11kg
138 121 614BW	139mm Black & White	20kg
138 121 663BW	152mm Black & White	13kg
138 121 733BW	168mm Black & White	24kg
138 121 793BW	193mm Black & White	28kg

Product details

• 3mm wall thickness - 60mm - 114mm and 152mm

Concrete in 300mm (below ground)

5mm wall thickness - 139mm, 168mm and 193mm

Also available bolt down or removable

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP

