



## Accessories Removable Socket Padlockable







Removable products are supplied with a socket, which will require casting into concrete.

Sockets are manufactured from galvanised mild steel.

Sockets exclude the padlock to secure.

Additional sockets can be purchased at extra cost, if required. Parts such as the lid can also be purchased at extra cost.

Integral locking sockets also available.

| Part Number | <u>Description</u>          | Size - Depth x Width x Height | Weight |
|-------------|-----------------------------|-------------------------------|--------|
| 138 500 085 | 100SQ SOCKET & LID ASS GALV | 150mm x 130mm x 220mm         | 4kg    |
| 138 500 087 | 160SQ SOCKET & LID ASS GALV | 210mm x 195mm x 300mm         | 8kg    |
| 138 500 089 | 225SQ SOCKET & LID ASS GALV | 280mm x 265mm x 300mm         | 13kg   |

|             |                            | For use with diameters |                         |  |
|-------------|----------------------------|------------------------|-------------------------|--|
| Part number | Mild Steel - Round         | Mild Steel - Square    | Stainless steel - Round |  |
| 138 500 085 | 48, 60, 76 and 90          | 50, 60, 70, 80 and 90  | 48, 60, 76 and 90       |  |
| 138 500 087 | 101, 114, 127, 139 and 152 | 100, 120 and 150       | 101, 114, 129 and 139   |  |
| 138 500 089 | 168, 193 and 219           | 100, 120 and 150       | 154, 168 and 204        |  |

## Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete.

Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.

Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

