MULTI-PURPOSE MIRRORS



TO VIEW 2 DIRECTIONS

CODE


P.A.S.® optics Code 915; R915



TECHNICAL SPECIFICATIONS

- > Lens: Polymir (515, R515) or PAS (915, R915) optics Ø 500 mm
- > Frame: white (515 and 915) or red (R515 and R915)
- > Packaging dimensions: 560x100x540 mm
- > Gross weight: 3.4 kg
- > Angle of convexity: for a field of vision of approximately 90° used at junctions where users are coming from 2 different
- > Maximum viewing distance betwee the mirror and viewer: approx 7 m
- > Fixing kit supplied
- > Full guarantee (mirror, frame and fixings)*
- > Manufactured in France
- > 100% recyclable

DIMENSIONS




GARANTEES



- > Unbreakable > light > unalterable > 3 year guarantee
- PAS 5 year 5 guarantee
- > Unbreakable > light > unalterable > Anti-UV treated > 5 year quarantee



FIXATION KIT DIAGRAM



Supplied complete with bolts and brackets kit, adaptable for walls or for posts 60 to 90mm in diameter. Kit is robust, tested to withstand winds of up to 183km/h. Easy to install, allowing precise adjustment of the position of the mirror.

RECOMMENDED INSTALLATION

